



Humiseal 2UV10 is a two component UV gellable poly Urethane system. This system can realize a tack free surface and functional strength with UV exposures as short as 20 seconds. The secondary reaction ensures shadowed areas are completely polymerized.

APPLICATIONS

Potting

FEATURES

SUBSTRATES

HumiSeal® 2UV10 Technical Data Sheet

Storage

HumiSeal® 2UV10 Part A and 2UV10 Part B should be stored in a cool, dry place between 8°C and 28°C in tightly closed containers. Keep from freezing.

Caution

Application of HumiSeal® 2UV10 should be carried out in accordance with local and national health and safety regulations. Use only in well-ventilated areas to avoid inhalation of vapor. Avoid contact with skin and eyes.

Consult SDS prior to use.

Contact HumiSeal®

HumiSeal North America

201 Zeta Drive
Pittsburgh, PA 15238
USA

Tel: +1 412-828-1500

Toll Free (US) 1-800-862-8652
sales@humiseal.com

HumiSeal Europe

505 Eskdale Road, IQ Winnersh
Berkshire RG41 5TU
UK

HumiSeal Technical Center

295 University Avenue
Westwood, MA 02090
USA

Tel: +1 781-332-0734

Fax: +1 781-332-0703

techsupport@humiseal.com